

Page | 1

Model	DF-12L
Manufacturer	Dongfeng
Retailer	CBM Builders
Website	http://cbmbd.com/product/df-12l
Function	Land Preparation



Specifications

Model of Power Tiller		Unit	DF-12L
Structure weight	Without rotavator	kg	350
	With rotavator		455
Working weight (With rotavator)			490
Turning speed of rototilling shaft		rpm	188
Overall dimensions(L×W×H)		mm	2680×960×1290
Number of blades		PCS	18
Rototilling width		mm	600
Riding system			Normal
Type of tractor			Single axle, dual-purpose for both traction & drive
Main gearbox			(3+1)×2
Traveling speed	Forward	km/h	1.5, 2.7, 4.4, 5.7, 10.2, 16.5
	Reverse		1.1, 4.1
Tire size			6.00-12
Wheel track		mm	800, 740, 640, 580(normally use 800)
Min. ground clearance		mm	185
Min. turning radius		m	0.9(with no rotavator)
Model of engine			S195N/ZS195N
Type of engine			Single-cylinder, Horizontal, 4-stroke, Direct injection, Water cooling
Bore ×stroke		mm	95×115
Total displacement		L	0.815
Compression ratio			17:01
Turning speed of crankshaft		rpm	2000
Rated output		hp	12
Specific fuel consumption		g/kW. h	265.2
Specific lube oil consumption		g/kW. h	≤2.72
Cooling mode			Condenser(Radiator)


USAID
FROM THE AMERICAN PEOPLE

TILLERS
international

Institute for the Prevention
of Postharvest Loss
University of Illinois


**NORTH CAROLINA
AGRICULTURAL AND TECHNICAL
STATE UNIVERSITY**

**UNIVERSITY OF
ILLINOIS**
URBANA-CHAMPAIGN

**FEED THE FUTURE
INNOVATION LAB**
Collaborative Research on
Sustainable Intensification

**MICHIGAN STATE
UNIVERSITY**
**KANSAS STATE
UNIVERSITY**